

Inspected By: \_\_\_\_\_ Date: \_\_\_\_\_

	Y	N
<b>UNIT INSPECTION</b>		
1. Make sure all exterior body stations are tightly affixed to columns. Body stations should not move when in use. Carriage bolts should sit flush to column.		
2. Remove access hatch to inspect anchor bolts. (Are they sitting flush to grade? Does the unit move when pushing on one side?)		
3. Inspect interior cables to make sure they're routed properly on pulleys and no visible damage.		
4. Inspect interior weight stack for any debris (Is anything jammed between weights or within weight stack assembly?)		
5. Test each position of assist mechanism (4 settings) Cycle each position to make sure it's working properly/smoothly		
6. Test each position on 45-degree back extension station (5 settings)		
7. Test Lexan gate to make sure it moves up/down with no issues		
8. Cycle weight stack pop pin to ensure it engages in each weight plate hole		
9. Lubricate interior guide rods with <i>Super Lube Multi-Purpose Synthetic Lubricant with Syncon (PTFE)</i> and cycle high/low. <b>DO NOT</b> use any type of grease lubricant on guide rods.		
10. Make sure all placards/frames are tightly affixed to columns		
<b>GENERAL</b>		
1. Warning labels are present and legible		
2. No insect, bird or animal infestation		
<b>FINISHES &amp; MATERIAL CONDITIONS</b>		
1. Metal surfaces are free of rust, chipped or peeling paint		
2. Surfaces are clean, free of graffiti and vandalism		
3. Free of bent, broken, missing parts, excessive wear		
4. Welds are intact and crack free		
<b>FASTENERS</b>		
1. Hardware is present, tight and fully engaged		
2. Cables are secure, properly routed and free from debris		
<b>STRUCTURAL MEMBERS</b>		
1. Footings/anchoring devices are secure and stable		
2. Structural members are sound and securely fastened		
<b>STEPPING COMPONENTS</b>		
1. Stepping surfaces are level, stable and clean		
<b>MOVING COMPONENTS</b>		
1. All moving components are in good condition and secure		
<b>OTHER</b>		
1. Use zones are clear of obstacles and debris		
2. Drainage holes are not blocked		
3. Padlock is locked, in good condition and untampered		

\*Contact Outdoor-Fit for Super Lube Spec