



# MAINTENANCE CHECKLIST



Inspected By: \_\_\_\_\_ Date: \_\_\_\_\_

	Y	N
<b>UNIT INSPECTION</b>		
1. Make sure carriage bolts holding handles and footpads are tightly affixed to the box. Carriage bolts should sit flush.		
2. Inspect anchor bolts. (Are they sitting flush to grade? Does the unit move when being pushed from one side?)		
3. Remove access hatch and visually inspect interior to ensure belting is sitting properly on all pulleys and there is no debris or visible damage.		
4. Remove any debris from inside of the machine.		
4. Step on foot pads and cycle Everest to make sure unit is working properly/smoothly		
<b>GENERAL</b>		
1. Warning labels signage present and legible		
2. No insect, bird or animal infestation		
<b>FINISHES &amp; MATERIAL CONDITIONS</b>		
1. Metal surfaces are free of rust, chipped or peeling paint		
2. Surfaces are clean, free of graffiti and vandalism		
3. Free of bent, broken, missing parts, excessive wear		
4. Welds are intact and crack free		
<b>FASTENERS</b>		
1. Hardware is present, tight and fully engaged		
2. Belting is secure, properly routed and free from debris		
<b>STRUCTURAL MEMBERS</b>		
1. Footings/anchoring devices are secure and stable		
2. Structural members are sound and securely fastened		
<b>STEPPING COMPONENTS</b>		
1. Stepping surfaces are level, stable and clean		
<b>MOVING COMPONENTS</b>		
1. All moving components are in good condition, secure, & lubricated		
2. *Optional* Lubricate interior bushing blocks with <i>Super Lube Multi-Purpose Synthetic Lubricant with Syncolon (PTFE)</i> and cycle unit. <b>DO NOT</b> use any type of grease lubricant		
<b>OTHER</b>		
1. Use zones are clear of obstacles and debris		
2. Padlock is locked, in good condition and untampered		

\*Contact Outdoor-Fit for Super Lube Spec